



# TELSMITH

an Astec Industries Co.

**Telsmith Incorporated**

10910 N. Industrial Drive

Mequon WI. 53092

Parts Toll Free: 1-800-688-6601

[www.telsmith.com](http://www.telsmith.com)

## LUBRICANT RECOMMENDATIONS FOR *T-Series* CONE CRUSHERS

Lubricant Type	Temperature Conditions °F/(°C)	Specification	Recommended Standard Lubricant	Recommended Synthetic Lubricant
Lube Oil	Return Oil Below 115°F (46°C)	ISO 100, AGMA 3 EP	Mobilgear 600 XP 100	Mobil SHC Gear 150
	Return Oil Above 115°F (46°C)	ISO 150, AGMA 4 EP	Mobilgear 600 XP 150	Mobil SHC Gear 150
Hydraulic Oil	Ambient Below 40°F (4°C)	ISO 32, HVI AW Low Pour Point	Mobil DTE 10 Excel 32	Mobil SHC 524
	Ambient Above 40°F (4°C)	ISO 68, Antiwear	Mobil DTE 26 or Mobil DTE 10 Excel 68	Mobil SHC 526
Buttress Thread Grease	All Ambient Temperatures	NGLI 2, with EP Additives, 3% Moly (min.)	Mobilgrease XHP 322 Mine	--

**\*\*CONSULT YOUR OWNERS MANUAL FOR CHANGE/REPLENISHMENT INTERVAL\*\***

For Mobil Product Information call 1-800-662-4525, or Visit [www.mobil.com/industrial](http://www.mobil.com/industrial)

1106044